

# Specifications

Size	A	B (Pole Dia.)	C	D	E	F
2'	24"	1.75"	28.25"	4.875"	4.25"	6.25"
3'	36"	1.75"	40.25"	4.875"	4.25"	6.25"
4'	48"	1.75"	52.25"	4.875"	4.25"	6.25"
5'	60"	1.75"	64.25"	4.875"	4.25"	6.25"
6'	72"	1.75"	76.25"	4.875"	4.25"	6.25"
8'	96"	1.75"	100.25"	4.875"	4.25"	6.25"
10'	120"	1.75"	124.25"	4.875"	4.25"	6.25"
12'	144"	1.75"	148.25"	4.875"	4.25"	6.25"
14'	168"	1.75"	172.25"	4.875"	4.25"	6.25"
16'	192"	1.75"	196.25"	4.875"	4.25"	6.25"
18'	216"	1.75"	220.25"	4.875"	4.25"	6.25"
20'	240"	1.75"	244.25"	4.875"	4.25"	6.25"

Field Dimensions for  
Fiberglass Pike Poles  
Duo-Safety Ladder Corp.  
Oshkosh, WI 54902

Rev 12/15

**Note:** Pike poles are designed for push and pull applications. This pole is hollow and not intended to be used as a pry bar.

